



The Os-series is an advanced digital high-speed camera designed to operate in the most demanding environments. The leading design feature of the OS7 is its compact size in combination with a wide data bus design. The OS7 is capable of delivering 1920 x 1280 images at high frame-rates (up to 4,200 fps). The high-capacity solid-state memory supports immediate data backup for maximum redundancy and direct streaming at several hundreds of frames per second.

KEY FEATURES

Maximum Resolution	1920 x 1280
Maximum FPS @ Maximum Resolution	2,700 fps
Image Storage @ Max Frame Rate (DDR 8)	6,002
Image Storage @ Max Frame Rate (SSD 512)	6,641
Streaming FPS @ Max Resolution	340 fps
Maximum FPS	84,000 @ 1920 x 16
Minimum Exposure Time	1µs
Sensitivity ASA/ISO	6000 ISO Mono 2000 ISO Color
Power Requirements	18-36 VDC
Operating Temperature	-40+50°C / -40+122°F

SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	17.5 x 11.8 mm
Sensor Format	1.3 inch
Pixel Size (micron)	9.12x9.12 µm
Pixel Depth	12 bit mono 36 bit color

INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL

OUTPUTS

Sync	Frame sync / Strobe
------	---------------------

FEATURES

Approx. Size	68 x 63 x 87 mm (W x H x L)
Approx. Weight	0.69 kg or 1.52 lbs
Shock/Vibration Rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Optional
Mount	C-Mount standard , F Adaptor optional

SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF

COMMUNICATION

Ethernet	1000BaseT
----------	-----------