



The Os-series is an advanced digital high-speed camera designed to operate in the most demanding environments. The leading design feature of the OS8 is its compact size in combination with a wide data bus design. The OS8 is capable of delivering 1600 x 1200 images at high frame-rates (up to 8,000 fps). The high-capacity solid-state memory supports immediate data backup for maximum redundancy and direct streaming at several hundreds of frames per second.

## KEY FEATURES

Maximum Resolution	1600 x 1200
Maximum FPS @ Maximum Resolution	8,000 fps
Image Storage @ Max Frame Rate (DDR 8)	8,275
Image Storage @ Max Frame Rate (SSD 512)	8,542
Streaming FPS @ Max Resolution	470 fps
Maximum FPS	194,000 @ 1600 x 16
Minimum Exposure Time	1µs
Sensitivity ASA/ISO	6000 ISO Mono 2000 ISO Color
Power Requirements	18-36 VDC
Operating Temperature	-40+50°C / -40+122°F

## SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 10.4 mm
Sensor Format	1.3 inch
Pixel Size (micron)	8.68x8.68 µm
Pixel Depth	12 bit mono 36 bit color

## INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL

## OUTPUTS

Sync	Frame sync / Strobe
------	---------------------

## FEATURES

Approx. Size	72 x 63 x 87 mm (W x H x L)
Approx. Weight	0.69 kg or 1.52 lbs
Shock/Vibration Rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Optional
Mount	C-Mount standard , F Adaptor optional

## SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF

## COMMUNICATION

Ethernet	1000BaseT
----------	-----------